



THE UNIVERSITY *of* EDINBURGH

Edinburgh Research Explorer

A talkative Potts attractor neural network welcomes BLISS words

Citation for published version:

Pirmoradian, S & Treves, A 2012, 'A talkative Potts attractor neural network welcomes BLISS words', *BMC Neuroscience*, vol. 13, no. Suppl 1, pp. P21. <https://doi.org/10.1186/1471-2202-13-S1-P21>

Digital Object Identifier (DOI):

[10.1186/1471-2202-13-S1-P21](https://doi.org/10.1186/1471-2202-13-S1-P21)

Link:

[Link to publication record in Edinburgh Research Explorer](#)

Document Version:

Publisher's PDF, also known as Version of record

Published In:

BMC Neuroscience

General rights

Copyright for the publications made accessible via the Edinburgh Research Explorer is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

The University of Edinburgh has made every reasonable effort to ensure that Edinburgh Research Explorer content complies with UK legislation. If you believe that the public display of this file breaches copyright please contact openaccess@ed.ac.uk providing details, and we will remove access to the work immediately and investigate your claim.



POSTER PRESENTATION

Open Access

A talkative Potts attractor neural network welcomes BLISS words

Sahar Pirmoradian*, Alessandro Treves

From Twenty First Annual Computational Neuroscience Meeting: CNS*2012
Decatur, GA, USA. 21-26 July 2012

Neuroscientists have observed that the human brain is comprised of neurons. We have observed that babies start speaking at an early age, yet no young animals, including pets, have so far been seen to speak, at least not in the articulated fashion of human babies. To understand this highly cognitive ability, many psycholinguistic data have been gathered, from behavioral, to neurolinguistic, to recent neuroimaging studies, each measuring macroscopic properties of the brain. Nevertheless, the challenging question remains unanswered of how such complicated behavior emerges from the microscopic (or mesoscopic) properties of individual neurons and of networks of neurons in the brain.

We would like to tackle this question by developing and analyzing a Potts attractor neural network model, whose units hypothetically represent patches of the cortex. The network has the ability to spontaneously hop (or latch) across memory patterns (which have been stored as dynamical attractors), thus producing an infinite sequence of patterns, at least in some regimes [1]. We would like to train the network with a corpus of sentences in BLISS [2]. BLISS is a scaled-down synthetic language of intermediate complexity, with about 150 words and about 40 rewrite rules. We expect the Potts network to generate sequences of memorized words, with statistics reflecting to some degree that of the BLISS corpus used in training it.

Before training the network on the corpus, the critical issues to be addressed, and the central ones here, are: how should the words be represented in a cognitively plausible manner in the network? how should the correlation between words, in terms of both meaning and statistical dependences, be reflected in their (neural) representations? how should two main characteristics of

a word, the meaning (semantic) and the syntactic properties, be represented in the network?

We represent words in a distributed fashion on 900 units, 541 out of which express the semantic content and the rest, 359 units, are representative of the syntactic characteristics of a word. The distinction between the semantic and syntactic characteristics of a word has been loosely inspired by a vast number of neuropsychological studies [3]. Further, several findings have indicated a distinction between the encoding of function words (i.e. prepositions, conjunctives, determiners, etc.) and content words (i.e. nouns, verbs, adjectives, ...) in the brain [4]. To implement a plausible model of the variable degree of correlation between word representations, we have used an algorithm comprised of two steps [5]: first, a number of vectors, called factors, are established, each factor influencing the activation of some of the units, by “suggesting” a particular state; second, the competition among these factors determines the activation state of each unit of a word.

The preliminary analysis of the produced patterns indicates the resemblance between the statistics of the representation of words and the patterns that can generate the latching behavior of the network. This is a promising step towards building a neural network that can spontaneously generate a sequence of words (sentences) with desired syntactic and semantic relationships between words in sentences.

Published: 16 July 2012

References

1. Russo Eleonora, Pirmoradian Sahar, Treves Alessandro: **Associative Latching Dynamics vs. Syntax**. *Adv in Cogn Neurodyn (II)* Springer; 2011, 111-115.
2. Pirmoradian Sahar, Treves Alessandro: **BLISS: an artificial language for learnability studies**. *Cogn Comput* 2011, **3**:539-553.
3. Shallice Tim, Cooper Richard: **The organisation of mind**. Oxford Univ Pr; 2011.

* Correspondence: pirmorad@sissa.it
Cognitive Neuroscience Sector, SISSA, Trieste, 34136, Italy

4. Shapiro Kevin A, Caramazza Alfonso: **Morphological Processes in Language Production**. *The Cognitive Neurosciences* MIT Pr; 2011, 777-788.
5. Treves Alessandro: **Frontal latching networks: a possible neural basis for infinite recursion**. *Cogn Neuropsych* 2005, **3**:276-291.

doi:10.1186/1471-2202-13-S1-P21

Cite this article as: Pirmoradian and Treves: **A talkative Potts attractor neural network welcomes BLISS words**. *BMC Neuroscience* 2012 **13**(Suppl 1):P21.

**Submit your next manuscript to BioMed Central
and take full advantage of:**

- Convenient online submission
- Thorough peer review
- No space constraints or color figure charges
- Immediate publication on acceptance
- Inclusion in PubMed, CAS, Scopus and Google Scholar
- Research which is freely available for redistribution

Submit your manuscript at
www.biomedcentral.com/submit

